## REMOVABLE TRIM BOARD DETAIL Cladding Moisture Barrier: Overlap Membrane 2" minimum. 'Duradek' Membrane: Fully adhered 8" minimum up wall Pre-finished metal flashing NOTE: Removable trim board: Min. 2" clearance from deck surface for wood, cementitious trims. PVC trims (drawn) can extend to deck. Fasten at least 3.5" above deck through butyl tape. SCALE: 6"=1'-0" AS A SUPPLIER OF FINISHED PRODUCT ONLY, DURADEK LTD. DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN, ENGINEERING, OR DIMENSIONS. THE NOTE: ARCHITECT, ENGINEER, SPECIFIER, CONTRACTOR OR OWNERS' REPRESENTATIVE MUST VERIFY ALL DIMENSIONS, SIZES & SUITABILITY OF DETAILS. **DURADEK LTD.** CANADA Bus: (604) 591-5594 Fax: (604) 591-3100 UNITED STATES Bus: (816) 421-5830 Fax: (816) 421-2924 25/08/08 SYSTEM: DRAWING No.: DATE: $\sqrt{0}$ 15-08 ALL ASSEMBLIES

REV. DATE: