



# D763-1 WATER BASED ADHESIVE

Duradek's D763-1 is a high performance trowel grade water-based adhesive specifically formulated for laminating and wrapping of unsupported polyvinyl chloride (PVC) films and a wide variety of papers, including impregnated films.



## Typical Physical Properties

- Colour: White
- Density: 8.8 - 9.2lb - mass /US Gallon
- PH: 3.4 - 4.6
- Shelf Life: 6 Months
- Solids Content (non-volatiles): 54 - 58%
- Viscosity: 22,500 - 27,500 cP

## END-USER DIRECTIONS

### Application Information

Surfaces must be clean, dry and exempt of dust, grease or other greasy contaminants.

1. Apply adhesive to deck surface only using trowel.
2. Lay membrane into wet glue.
3. Bond together using hands, spreader, or roller.

### Clean Up

Whenever possible, clean up product before it dries, using warm water. If dry, use hot water and scraper.

### Freezing Sensitivity

Store above 40°F (4°C). Do not allow to freeze, cannot be rejuvenated.

### Storage life

Storage temperatures between 60-80°F are suggested. Higher storage temperatures will shorten life.

### Safety

Eye contact may cause irritation. Prolonged skin contact may cause irritation. No expected harmful effects from inhalation of vapors. Consult material safety data sheet for further information.